




**Xitanium** Long-lasting and low maintenance, LED-based light sources are an excellent solution for all lighting applications. For optimal performance, these solutions require reliable drivers matching the long lifetime of the LEDs. The Advance Xitanium LED outdoor driver portfolio offers a range of products specially designed to operate LED solutions in outdoor applications. These drivers are designed for hard-wired integration into outdoor luminaires for the most rugged applications. They operate to specification under wide temperature and electrical ranges to ensure reliability.

### Specifications


Input Voltage (Vac)	Output Power (W)	Output Voltage (V)	Output Current (A)	Efficiency@ Max Load and 75°C Case	Max Case Temp. (°C)	Input Current (A)	Max. Input Power (W)	THD @ Max Load (%)	Power Factor @ Max Load	Surge Protection (Combi-Wave, KV)	Envir. Protection Rating	Dimming	Dimming Range (with specified dimmers)	Min. Output Current (A)
120	30	12-40	0.1 - 1.2	86	90°C	0.31	35	<15%	>0.95	6	UL damp & dry, Type HL	0-10V Analog Class 1 and 2 Wiring	10% ~ 100%	0.05
277				86		0.14								

### Enclosure

	In. (mm)
Case Length (L2)	5.51 (140)
Case Width (W)	1.79 (45.5)
Case Height (H)	1.12 (28.5)
Mounting Length (M1)	5.98 (152)
Overall Length (L1)	6.61 (168mm)



### Wiring Diagram



Intertek  
Class P  
Conforms to UL STD 8750  
Certified to CAN/CSA STD  
C22.2 No. 250.13

Class P  
LED class 2 output  
For Dry and Damp Location

# Xitanium XI030C120V040BSJ1

## 30W 1.2A 0-10V Dimming

### Features

- 50,000+ hour lifetime<sup>1</sup>
- Programmable output current through SimpleSet
- 6kV combi-wave surge rating to comply with ANSI C28.77-5 CAT C low
- Configurable Driver Thermal Limit (DTL)

### Benefits

- Enables long life luminaire designs
- Fast and simple way of programming
- No external surge protection required to pass C82.77-5 CAT low

### Application

- Wallpacks
- Parking garages (interior and exterior)
- Floodlights

### Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

### Product Data

Order Information	
Full Product Code	XI030C120V040BSJ1, 12NC 929001743313
Line Frequency	50/60Hz
Min. Mains Voltage Operational	108 Vac
Max. Mains Voltage Operational	305 Vac
Output Information	
Maximum Open Circuit Voltage	45Vdc
Output Current Ripple (ripple = peak to average / average)	15% max. @ max. Iout
Output Current Tolerance (in performance window)	<5%
Protections	Short Circuit, Open Circuit Protection for LED + and LED – and Temperature Foldback
Features	
0-10V Dimming	150µA (±3%) source current from driver. See dim curve for detail.
AOC (Adjustable Output Current)	0.1 -1.2 via SimpleSet (Factory Default at 1.05A)
Additional SimpleSet Configurable Features	Adjustable Min Dim Level, OEM Write Protection, Driver Thermal Limit (DTL)
Environment & Approbation	
Operating Ambient Temp. Range	-40°C to +55°C
Max. Case Temperature (Tcase)	85°C for life & 90°C for UL
Agency Approbations	UL 8750, CSA 250.13, UL Listed, ETL Class P
Electromagnetic Compliance	FCC Title 47 Part 15 Class A
Audible Noise	<24dB Class A
Weight	0.795 Lbs / 0.361 Kgs

1. Advance Xitanium LED drivers are manufactured to engineering standards correlating to a designed and average life expectancy of 50,000 hours of operation at maximum rated case temperature. Minimum 90% survivals based on MTBF modeling.

# Xitanium XI030C120V040BSJ1

## 30W 1.2A 0-10V Dimming

### Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

### 0-10V Dimming Curve


Dimming source current from the driver: 150µA (@ 0<Vdim<8V)

Minimum dim level: 10% of Iout

Maximum output voltage on the dimming wires: 12V

### Approved Dimmer List

Manufacturer	Manufacturer Part Number
Lutron	Visit <a href="http://www.lutron.com/advance">www.lutron.com/advance</a> for a list of dimmers (Mark VII) that will work with this driver
Leviton	IllumaTech IP7 series
Advance	Sunrise - SR1200ZTUNV




# Xitanium XI030C120V040BSJ1

30W 1.2A 0-10V Dimming

## Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

## Driver Output Window




# Xitanium XI030C120V040BSJ1

30W 1.2A 0-10V Dimming


## Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

## Output Current Vs. Driver Case Temperature



## Driver Lifetime vs. Driver Case Temperature




# Xitanium XI030C120V040BSJ1

## 30W 1.2A 0-10V Dimming


### Performance Characteristics

Based on measurements on a typical sample at 75°C case. The accuracy of the measurements is within the tolerance of the measurement instruments.

### Efficiency Vs. Output Voltage at 120Vac



### Efficiency Vs. Output Voltage at 277Vac




# Xitanium XI030C120V040BSJ1

## 30W 1.2A 0-10V Dimming


### Performance Characteristics

Based on measurements on a typical sample at 75°C case. The accuracy of the measurements is within the tolerance of the measurement instruments.

### Power Factor Vs. Output Power




### Total Harmonic Distortion (THD) Vs. Output Power



# Xitanium XI030C120V040BSJ1

30W 1.2A 0-10V Dimming

## Inrush Current Info



$V_{in}$	$I_{peak}$	$T (@ 10\% \text{ of } I_{peak})$
120 Vrms	14 A	150 $\mu$ s
277 Vrms	37 A	400 $\mu$ s

Inrush current is measured at peak of the corresponding line voltage.  
Source impedance per NEMA 410.

## Lightning Surge Info

ANSI Surge Type	Differential Mode (L-N)	Common Mode (L-G, N-G, L&N-G)
1.2/50 $\mu$ s Combination Wave (w/t 2 $\Omega$ )	6kV	6kV

## Isolation

Isolation	Input	Output	0-10V	Enclosure
Input	NA	2xU+1kV	2.5kV	2xU+1kV
Output	2xU+1kV	NA	2.5kV	2xU+1kV
0-10V	2.5kV	2.5kV	NA	2.5kV
Enclosure	2xU+1kV	2xU+1kV	2.5kV	NA

U = Max. input voltage

