

AMY-35-WW-B

~60° wide beam. Assembly with holder B compatible with Ø35 mm BJB + B+W connectors. Black version.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 34.9 mm
Height	11 mm
ROHS compliant	yes ⓘ




MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
AMY-35-WW	Single lens	PMMA	clear	
AMY-35-HLD-B	Holder	PC	black	











ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CP17973_AMY-35-WW-B » Box size: 480 x 280 x 300 mm	1320	132	66	9.6



See also our general installation guide: www.ledil.com/installation_guide


PHOTOMETRIC DATA (MEASURED):

<p></p> <p>LED Vesta TW 6mm DP FWHM / FWTM 50.0° / 83.0° Efficiency 87 % Peak intensity 1.1 cd/m LEDs/each optic 1 Light colour Tunable White Required components: Bender Wirth: 504 Type B35L</p>		
<p>CITIZEN</p> <p>LED CLU700/701/702 FWHM / FWTM 51.0° / 82.0° Efficiency 91 % Peak intensity 1.1 cd/m LEDs/each optic 1 Light colour White Required components: Bender Wirth: 634a Bayonet35L</p>		
<p>CITIZEN</p> <p>LED CLU700/701/702 FWHM / FWTM 52.0° / 83.0° Efficiency 90 % Peak intensity 1.1 cd/m LEDs/each optic 1 Light colour White Required components: BJB: 47.360.1020</p>		
<p></p> <p>LED CMU10xx FWHM / FWTM 58.0° / 95.0° Efficiency 89 % Peak intensity 0.9 cd/m LEDs/each optic 1 Light colour White Required components: BJB: 47.360.1020</p>		

PHOTOMETRIC DATA (MEASURED):




LED CTM-9 (Tunable White)
FWHM / FWTM 57.0° / 93.0°
Efficiency 85 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour Tunable White
Required components:
Bender Wirth: 495 Type B35L



PHOTOMETRIC DATA (SIMULATED):


CITIZEN

LED CLL02x/CLU02x (LES10)
 FWHM / FWTM 58.0° / 88.0°
 Efficiency 89 %
 Peak intensity 0.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 BJB: 47.360.1020




CITIZEN

LED CLU7A2 (LES 4.2mm)
 FWHM / FWTM 52.0° / 78.0°
 Efficiency 93 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 BJB: 47.360.1020




CITIZEN

LED CLU7B2
 FWHM / FWTM 53.0° / 79.0°
 Efficiency 93 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 BJB: 47.360.1020



CREE LED

LED CMA1306
 FWHM / FWTM 55.0° / 82.0°
 Efficiency 92 %
 Peak intensity 1.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 Bender Wirth: 634c Bayonet35L



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)